


A30 R - Self-propelled Tank Cleaner

CONT



Part No.	Max. flow rate	Min. overall Ø	Weight
25.3300.12	12 l/min - 3.1 USGpm	60 mm - 2.36 in	2030 gr. - 71.61 oz.
25.3300.15	15 l/min - 3.9 USGpm	60 mm - 2.36 in	2030 gr. - 71.61 oz.
25.3300.18	18 l/min - 4.6 USGpm	60 mm - 2.36 in	2030 gr. - 71.61 oz.
25.3300.25	25 l/min - 6.5 USGpm	60 mm - 2.36 in	2030 gr. - 71.61 oz.
25.3300.33	33 l/min - 8.6 USGpm	60 mm - 2.36 in	2030 gr. - 71.61 oz.

Common Features

Inlet	1/2 Bsp F
Rated Pressure	140 bar - 14 MPa - 2000 psi
Min. operating pressure	30 bar - 3 MPa - 435 psi
Permissible Pressure	160 bar - 16 MPa - 2300 psi
Rated Flow Rate	33 l/min - 8.7 USGpm
Rated Temperature	90 °C - 195 °F
Material	Stainless steel 303
Nozzle type	4 × M4
Rated rotation speed	30 giri/min - 0 RPM
Max. Rpm	30 giri/min - 0 RPM